


AMBITION

Technical details / Technische Daten

Tuft gauge / Teilung Deling / Galga	1/10 loop pile
Pilecomposition / Material Poolsamenstelling / Composición fibra	100% PA SDN
Primary backing / Träger Tuftdoek / Backing Primario	Non Woven
Secondary backing / Rückenausstattung Rug / Acabado	Bitumen
Dimensions / Abmessungen Dimensies / Dimensiones	50 x 50 cm ±1% 25 x 100 cm
Pile height / Polhöhe Poolhoogte / Altura del hilo	3 mm
Pile density / Pol-Rohdichte Pooldichtheid / Densidad	0.137 gr/cm ³
Pile weight / Oberflächen-/Florgewicht Poolgewicht / Peso del hilo	785 gr/m ²
Total weight / Gesamtgewicht Totaal gewicht / Peso total	4540 gr/m ² ±15%
Total height / Totale Höhe/Gesamtdicke Totale hoogte / Altura total	5 mm
Number of knots / Noppenzahl Aantal noppen / Puntadas	259000 /m ² -7.5% .+10%
Use Area / Verwendungsbereich Gebruik zone / Área de Uso	Extreme / Heavy (33)
Light fastness / Lichtechtheit Lichtechtheid / Solidez a la luz	≥ 5
Weareability / Reibechtheit Wrijfchtheid / Resistencia a la fricción	≥ 4
Water fastness / Wasserechtheit Waterechtheid / Resistencia al agua	≥ 4
Fire classification / Brandverhalten Brandclassificatie / Clasificación al fuego	Bfl-S1 1658-CPR-3134
Pictures / Bilder Foto's / Pictures	www.condorcontract.com



Condor Carpets
Randweg 14
8064 RW Hasselt

EN1307
DOP: C-003RBA215
Reaction to fire: Bfl-s1
Slip resistance: DS
EN 14041:2004
Resilient floor covering to be
used within a building



Condor Carpets bv
Randweg 14, 8061 RW
P.O. Box 21, 8060 AA
Hasselt, The Netherlands

T (+31) 38 447 89 11
F (+31) 38 447 89 22
E info@condorcarpets.nl
W www.condorcontract.com

WWW.CONDORCONTRACT.COM