



SCHATEX CITY

A synthesis of elegance and simplicity

The SCHATEX City carpet tile collection stands out because of a fine and elegant loop with a mottled colour appearance. The labour intensive tufting process guarantees a high level of robustness, which is improved even further through the reinforced fibreglass backing. SCHATEX City is the ideal carpet tile for use in the home, but is also a good choice for commercial use in areas with occasional or moderate use. Flame resistant (Cfl-S1) and suitable for use with castor wheeled chairs, these carpet tiles are composed of structured loops capable of meeting every demand. In addition, the especially thick surface structure makes for a pleasant walking comfort and a harmonious room experience. SCHATEX City has another benefit: installing these tiles is child's play – simply lay these tiles on an even, flat floor and you're finished!

- Carpet tiles with tufted loop piles
 - Mottled colour effect
 - Particularly thick surface
 - Flame resistant (Cfl-S1 in accordance with EN ISO 9239-1)
 - Suitable for use with office chairs
 - Especially robust reinforced fibreglass backing
 - Total thickness: 6.5 mm
-

SPECIFICATION



Specification SCHATEX City

Construction		Loop Pile
Yarn		100% Polypropylene
Yarn Weight		540 g/m ² ± 5%
Pile Thickness	ISO 1766	2.6 / 3.3 mm ± 5%
Tuft Density	ISO 1763	± 195000/m ²
Backing		Reinforced Fibreglass Backing
Total Thickness	ISO 1765	6.5 mm ± 5%
Total Weight		3900 g/m ² ± 7.5%
Dimension		50 x 50 cm
Tiles per Box		20

Performance

Classification	EN 1307	31 (Contract – light use)
Castor Chair Test	EN 985	A: continuous use
Slip Resistance		class DS
Vettermann Test	ISO TR 10361 / EN 1471	pass
Thermal Insulation	ISO 8302	0.08 m ² K/W
Dimensional Stability	EN 986	pass
Underfloor Heating		qualified
Electrical Resistance	ISO 6356	antistatic
Fire Resistance	EN ISO 11925-2 / EN ISO 9239-1	C _{fl} – s1 (hardly inflammable)
Colour Fastness	ISO 105 B02	7-8

Specifications



Colours

Light Beige 2202	Black 2214	Anthracite 2212	Grey 2216
Red 2226	Green 2242	Beige 2205	Blue 2223

Preliminary Specification

Best results are obtained when cleaned with a dry shampoo method.

→ **see Care Sheet**

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30m² it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

→ **see Installation Instruction**

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.