



SCHATEX PREMIUM

A union of comfort, lustre and elegance

SCHATEX Premium combines all optical and technical qualities in one carpet tile. The soft, fluffy, two-toned frieze velour cut pile tile is made up of very tightly twisted lustrous yarn, which seems to change its colouring depending on the fall of the light. In an onerous tufting procedure individual yarns were twisted to a different extent. The very elegant high and low effect achieved in this way makes SCHATEX Premium truly an optical experience. These cut pile tiles are particularly thick and are distinguished on the basis of the use of exceptional yarn material with an extremely high pile weight (1010 g/m²) in production. The homely soft surface guarantees an especially high walking comfort. SCHATEX Premium carpet tiles are quickly and easily installed. The top class fibreglass backing is very robust and because of the high weight is also very stable and protected against slipping. These tiles are manufactured using yarn made up of 100% high quality Polyamid, which increases the hardwearing capabilities further. SCHATEX Premium, an elegant carpet tile, which is best suited for heavy traffic business and residential areas.

- Fluffy frieze velours with tightly twisted yarn
 - Understated high- and deep-effect created by twisting the separate yarns to varying degrees of during the tufting process.
 - Very high workmanship using quality yarn materials (100% Polyamide)
 - High pile weight
 - Great walking comfort
 - Ideally suited for commercial use (Use Area Class 32)
 - Flame retardant (B₁-S1 in accordance with EN ISO 9239-1)
 - Robust fibreglass backing
 - High total weight: 4,600 g/m²
-

SPECIFICATION



Specification SCHATEX Premium

Construction		Fizzled Velour
Yarn		100% Polyamide
Yarn Weight		1010 g/m ² ± 5%
Pile Thickness	ISO 1766	5.1 mm ± 5%
Tuft Density	ISO 1763	± 187.200/m ²
Backing		Reinforced Fibreglass Backing
Total Thickness	ISO 1765	8.8 mm ± 5%
Total Weight		4600 g/m ² ± 7.5%
Dimension		50 x 50 cm
Tiles per Box		20

Performance

Classification		32 (Contract – light use)
Castor Chair Test	EN 985	A: continuous use
Slip Resistance		class DS
Vettermann Test	ISO TR 10361 / EN 1471	pass
Thermal Insulation	ISO 8302	0.088 m ² K/W
Dimensional Stability	EN 2551	pass
Underfloor Heating		qualified
Electrical Resistance	ISO 6356	antistatic
Fire Resistance	EN ISO 11925-2 / EN ISO 9239-1	B _{fl} – s1 (hardly inflammable)
Colour Fastness	ISO 105 B02	7.0

Specifications



CE	Scharpenack GmbH	EN 14041
	Hochstraße 10	1658 - CPR - 3013
	42105 Wuppertal	

Colours

Blue 2122	Anthracite 2114
Grey 2117	Red 2130
Brown 2106	Beige 2102

Preliminary Specification

Best results are obtained when cleaned with a dry shampoo method.

→ **see Care Sheet**

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30m² it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

→ **see Installation Instruction**

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.