



SCHATEX PRESTIGE

The indestructible carpet tile

The new Prestige carpet tiles from SCHATEX®, which are made from top quality Polyamide yarn, guarantee robustness and a long product life. Whether in residential, office, restaurant or other commercial areas the needle felt hair tiles can be used in a huge variety of ways and settings (Use Area Classification 33). The SCHATEX Prestige tiles are equipped with the very stable and innovative reinforced fibreglass backing. Fire resistant (C_{ir}-S1), suitable for being used with office chairs and anti-static – SCHATEX Prestige can more than cope with daily requirements. The use of adhesives is not necessary. SCHATEX Prestige is also convincing from an optical point of view: twelve trendy colours, which shimmer under light fall, make for a harmonious room experience, which can be further intensified through the combining of various colours or laying these tiles in a chessboard pattern.

- Very hardwearing needle felt hair tiles
 - Suitable for heavy usage (Use Area Classification 33)
 - Consists 100% of high quality polyamide yarn
 - Available in 12 modern colours
 - Total thickness: 9 mm
 - Fire resistant (C_{ir}-S1 in accordance with EN ISO 9239-1)
 - DS-Anti-Slip
 - Good thermal characteristics (0.14 m² K/W in accordance with ISO 8302)
 - Simply and quickly installed
 - Measurement: 50 x 50 cm
 - Total weight: 5,000 g/m²
-

SPECIFICATION



Specification SCHATEX Prestige

Construction		Hair Fleece
Yarn		100% Polyamide
Yarn Weight		870 g/m ² ± 7.5%
Pile Thickness	ISO 1766	4.2 mm ± 5%
Backing		Reinforced Fibreglass Backing
Total Thickness	ISO 1765	9 mm ± 5%
Total Weight		5000 g/m ² ± 7.5%
Dimension		50 x 50 cm
Tiles per Box		20

Performance

Classification	EN 1307	33 (Contract – heavy use)
Castor Chair Test	EN 985	A: continuous use
Slip Resistance		class DS
Vettermann Test	ISO TR 10361 / EN 1471	pass
Thermal Insulation	ISO 8302	0.14 m ² K/W
Dimensional Stability	EN 986	pass
Underfloor Heating		qualified
Electrical Resistance	ISO 6356	antistatic
Fire Resistance	EN ISO 11925-2 / EN ISO 9239-1	C _{fl} – s1 (hardly inflammable)
Colour Fastness	ISO 105 B02	> 5

Specifications



CE	Scharpenack GmbH	EN 14041
	Hochstraße 10	1658 - CPR - 3013
	42105 Wuppertal	

Colours

Black 1115	Grey 1116	Dark Brown 1109	Orange 1135
Green 1143	Purple 1138	Yellow 1148	Blue 1123
Anthracite 1111	Red 1128	Dark Green 1145	Light Brown 1106

Preliminary Specification

Best results are obtained when cleaned with a dry shampoo method.

→ **see Care Sheet**

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30m² it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

→ **see Installation Instruction**

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.