



SCHATEX TRAFFIC

The great value solution for business and trade fair needs

SCHATEX Traffic convinces in every aspect. The hardwearing needle-velour tiles are, due to their excellent technical characteristics, ideally suited for use in busy commercial and trade fair areas (Use Area Classification 33 according to EN 1307). Suitable for use with castor wheeled furniture, flame retardant to C_{fl}-S1, DS Anti-slip, in short SCHATEX Traffic is the affordable, beginners quality carpet, which can be installed anywhere. Shimmering Polypropylene yarn makes for a dignified and elegant spatial experience, which can be even further enhanced by the laying of these tiles in a chessboard pattern. Thanks to the innovative reinforced fibreglass backing material these carpet tiles can be installed quickly and easily.

- The low-cost, robust tile
 - Ideal for business and trade hall settings (Use Area Class 33 according to EN 1307)
 - Lightly mottled colour pattern for a discrete room décor
 - Suitable to use with castor wheels (EN 985)
 - Innovative reinforced fibreglass backing
 - Very flame resistant (C_{fl}-S1 according to EN ISO 9239-1)
 - DS Anti-Slip
 - Pile fibre material: 100% Polypropylene
 - Measurements: 50 x 50 cm
 - Total thickness: 5.00 mm (ISO 1765)
-

SPECIFICATION



Specification SCHATEX Traffic

Construction		Needle Velour
Yarn		100% Polypropylene
Yarn Weight	ISO 8543	500 g/m ² ± 7.5%
Pile Thickness	ISO 1766	3.0 mm ± 5%
Backing		Reinforced Fibreglass Backing
Total Thickness	ISO 1765	5 mm ± 5%
Total Weight	ISO 1763	3500 g/m ² ± 7.5%
Dimension		50 x 50 cm
Tiles per Box		20

Performance

Classification	EN 1307	33 (Contract – heavy use)
Castor Chair Test	EN 985	A: occasional use
Slip Resistance		class DS
Vettermann Test	ISO TR 10361 / EN 1471	pass
Thermal Insulation	ISO 8302	0.08 m ² K/W
Dimensional Stability	EN 986	pass
Underfloor Heating		qualified
Electrical Resistance	ISO 6356	antistatic
Fire Resistance	EN ISO 11925-2 / EN ISO 9239-1	C _{fl} – s1 (hardly inflammable)
Colour Fastness	ISO 105 B02	7-8

Specifications



CE	Scharpenack GmbH	EN 14041
	Hochstraße 10	1658 - CPR - 3012
	42105 Wuppertal	

Colours

<p>Blue</p> <p>1723</p>	<p>Anthracite</p> <p>1714</p>
<p>Grey</p> <p>1717</p>	<p>Beige</p> <p>1703</p>

Preliminary Specification

Best results are obtained when cleaned with a dry shampoo method.

→ see Care Sheet

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30m² it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

→ see Installation Instruction

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.